

## Lelystad

No 635 Aged & Bandsawn White Oiled Textured European Oak

### Grading

#### Rustic grade

Extra rustic. Natural colour variation is allowed, and sapwood is permissible. Sound knots are acceptable and filler will be used to fill knots, cracks and sound splits.



### Product Details

Product Code	No 635
Collection	Vintage & Aged
Construction	Engineered Multi-Ply
Specie	European Oak
Finish	Satin Hardwax Oiled
Top Layer	4mm (15mm thick) 6mm (20mm thick)
Bottom Layer	Birch Plywood
Surface	Brushed & Bandsawn
Thickness	15mm
Width	220mm
Length	600-3000mm (80% 1800mm +)
Grade	Rustic
Edges	Four Side Micro-Bevel
Profile	Tongue and Groove
Pack Size	Random

### Installation

Glued Down	Yes* (recommended)
Secret Nailed	Yes*
Floated	Yes*
Over UFH	Yes* (surface must not exceed 27°C)

### Technical

Janka Hardness Rating	1,120 lbf (4,980N)
Slip resistance	64/30 PTV** (BS7976-2:2002)
Origin	Europe
Thermal Conductivity	λ 0.15-0.17 W/m2 K (EN12664)
Responsible Certificate	Please contact us for details
Finish Information	Please contact us for details
Formaldehyde Emmision	E1 (EN717-1)
Reaction to Fire Certificate	Please contact us for details
Maintenance	Maintenance instructions are available for this product via our website or office.

\* Subject to correct installation and compatible subfloor, heating system and control. (See our installation over underfloor heating guide for details)

\*\* Slip resistances are based on third party sample tests, and should be use for guidance only.

This technical data sheets was written by Eden Clay. All information contained in this data sheet was correct at the time of writing and publication. Eden Clay reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.