

Technical data sheet

Natura Herringbone

No 262 Satin Oiled Natural European Oak

Grading

Natural grade

Natural colour variation is allowed, and some sapwood is permissible. Sound knots up to a maximum diameter of 60mm and small open knots and splits are acceptable.



Product Details

Product Code	No 262
Collection	Herringbone & Chevron
Construction	Engineered Multi-Ply
Specie	European Oak
Finish	Satin Hardwax Oil
Top Layer	4mm
Bottom Layer	Birch Plywood
Surface	Brushed
Thickness	15mm
Width	70mm
Length	280mm
Grade	Nature
Edges	Four Side Micro-Bevel and Aged
Profile	Tongue and Groove
Pack Size	0.784m2

Installation

Glued Down	Yes* (recommended)
Secret Nailed	Yes*
Floated	Yes*
Over UFH	Yes* (surface must not exceed 27°C)

Technical

Janka Hardness Rating	1,120 lbf (4,980N)
Slip resistance	64/30 PTV** (BS7976-2:2002)
Origin	Europe
Thermal Conductivity	λ 0.15-0.17 W/m2 K (EN12664)
Responsible Certificate	Please contact us for details
Finish Information	Please contact us for details
Formaldehyde Emmision	E1 (EN717-1)
Reaction to Fire Certificate	Please contact us for details
Maintenance	Maintenance instructions are available for this product via our website or office.

* Subject to correct installation and compatible subfloor, heating system and control. (See our installation over underfloor heating guide for details) ** Slip resistances are based on third party sample tests, and should be use for guidance only.

This technical data sheets was written by Eden Clay. All information contained in this data sheet was correct at the time of writing and publication. Eden Clay reserves the right to change the specification at any time without prior notice to third parties. Photographs used in this data sheet are for reference only. No rights can be derived from them.

Marq Andrews Ltd, T/A Eden Clay, Unit 1& 2 Lawness Barn, Mountnessing Road, Billericay, Essex, CM12 0TS. T +44(0)1277 624966 E info@edenclay.co.uk www.edenclay.co.uk